

### Airless trysky - TITAN SC-6



Tryska	Šírka striekaného lúča (cm)		Výkon (l / min)	Vrtanie (mm / inch)	Odporúčaný filter	Využitie
	nová	opotrebovaná				
107	5	3	0,2	0,18 / 0,007	200 až 150 Mesh	Moridlá
207	10	5				
109	5	3	0,3	0,23 / 0,009	150 až 100 Mesh	Laky Moridlá
209	10	7				
309	15	10				
409	20	15				
509	25	20				
111	5	3	0,5	0,28 / 0,011	150 až 100 Mesh	Emailové farby Laky Uretány
211	10	7				
311	15	10				
411	20	15				
511	25	20				
611	30	25	0,7	0,33 / 0,013	100 až 75 Mesh	Akryláty Emailové farby Laky Uretány
113	5	3				
213	10	7				
313	15	10				
413	20	15				
513	25	20	0,9	0,38 / 0,015	100 až 75 Mesh	Akryláty Emailové farby Laky Uretány
613	30	25				
115	5	3				
215	10	7				
315	15	10				
415	20	15	1,2	0,43 / 0,017	75 až 50 Mesh	Akryláty Emailové farby Latexy Uretány
515	25	20				
615	30	25				
117	5	3				
217	10	7				
317	15	10				
417	20	15				
517	25	20				
617	30	25				

Tryska	Šírka striekaného lúča (cm)		Výkon (l / min)	Vrtanie (mm / inch)	Odporúčany filter	Využitie
	nová	opotrebovaná				
119	5	3				
219	10	7				
319	15	10				
419	20	15	1,5	0,48 / 0,019	50 Mesh	Akryláty Latexy
519	25	20				
619	30	25				
221	10	7				
321	15	10				
421	20	15	1,8	0,53 / 0,021	50 Mesh	Akryláty Latexy
521	25	20				
621	30	25				
223	10	7				
323	15	10				
423	20	15	2,2	0,58 / 0,023	50 až 30 Mesh	Protipožiarne
523	25	20				
623	30	25				
225	10	7				
325	15	10				
425	20	15	2,5	0,64 / 0,025	50 až 30 Mesh	Protipožiarne Vyrovnávacie štrky
525	25	20				
625	30	25				
327	15	10				
427	20	15	3,0	0,69 / 0,027	50 až 30 Mesh	Protipožiarne Vyrovnávacie štrky
527	25	20				
627	30	25				

Šírka striekaného lúča sa určuje vo vzdialenosti 30 cm od povrchu.

<https://www.gamin.sk/airless-trysky-titan-sc6/>